KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system	
Adjustment options:	External calibration
Linearity:	3 g
Load cell connection:	6-Leiter
Number of weighing ranges:	1
Readability [d]:	1 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	1 g
Resolution:	30000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	2 h
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	5,500 cm

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions		
Counting function:	yes	
Data hold function:	yes	
Help function on the display:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal	yes	

Weighing with tolerance range: yes

Environmental conditions

Maximum humidity:

Maximum operating temperature:

Minimum ambient temperature:

40 °C

Minimum humidity:

0 %

Power supply

Charging time: 12 h

Input voltage: 220 V - 240 V AC 50 Hz

Mains adapter/adapter included: EURO
Operating time (Backlight off): 80 h
Operating time (Backlight on): 40 h

Rechargeable battery: Rchrg. battery optional

(factory)

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Category

Brand: KERN
Category: Balances
Product Group: Industiral scale

Packaging & shipping

Delivery: 24 h

Dimensions packaging (WxDxH): 500 x 775 x 240 mm

Gross weight: 23 kg

Net weight: 20,500 kg

Shipping method: Parcel service

Construction

Cable length of display device: 2,500 m

Dimensions of display device 232 x 150 x 80 mm
(WxDxH):

Dimensions of weighing plate 500 x 400 x 123 mm
(WxDxH):

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes

Wall mount: yes
Weighing surface (WxD): 500 x 400 mm

weighing program): KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49–(0)7433 - 99 33-0 · www.kern-sohn.com

KERN IXS30K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme STANDARD MOVE IP 65 IP 68 TOL 230 V CAL EXT PCS SUM 1 DAY 2 DAYS **OPTION** DAkkS +3 DAYS **FACTORY** - ARRA - 6886 RS 232 RS 485 ACCU +3 DAYS