KERN IXS60K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system			
Adjustment options:	External calibration		
Linearity:	6 g		
Load cell connection:	6-Leiter		
Number of weighing ranges:	1		
Readability [d]:	2 g		
Recommended adjusting weight:	60 kg (M1)		
Repeatability:	2 g		
Resolution:	30000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-60 kg		
Warm up time:	2 h		
Weighing capacity [Max]:	60 kg Strain gauge		
Weighing system:			
Weighing units:	kg		
Display			
Display digit height:	5,500 cm		
Counting			
Counting resolution:	30000		
Mininum piece weight at piece counting (Laboratory:	2 g		
Mininum piece weight at piece counting (Normal):	20 g		
Functions			
Counting function:	yes		
Data hold function:	yes		
Help function on the display:	yes		
Peak function:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal weighing program):	yes		

Weighing with tolerance range:	Vec		
weighing with tolerance range.	yes		
Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0 %		
Power supply			
Charging time:	12 h		
Input voltage:	220 V - 240 V AC 50 Hz		
Mains adapter/adapter included:	EURO		
Operating time (Backlight off):	80 h		
Operating time (Backlight on):	40 h		
Rechargeable battery:	Rchrg. battery optional (factory)		
Service			
Adjustment at the location of installation	n:961-249		
DALLO Contification	000 400		
DAkkS Certificate:	963-129		
Category			
Brand:	KERN		
Category:	Balances		
Product Group:	Industiral scale		
Packaging & shipping			
Delivery:	24 h		
Dimensions packaging (WxDxH):	490 x 770 x 255 mm		
Gross weight:	23,800 kg		
Net weight:	20,500 kg		
Shipping method:	Parcel service		
Construction			
Cable length of display device:	2,500 m		
Dimensions of display device (WxDxH):	232 x 150 x 80 mm		
Dimensions of weighing plate (WxDxH):	500 x 400 x 123 mm		
Level indicator:	yes		
Material weighing plate:	stainless steel		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	500 x 400 mm		

KERN IXS60K-3L



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

Piktogramme

STANDARD

CAL EXT PCS	SUM	-√+ © ৢ৽ TOL	Move	665	000 IP 68	230 V	DMS
1 DAY							
OPTION							

DAkks +3 days

FACTORY

	• 888. •	*		Μ	
RS 232	RS 485	BT	ACCU	+3 DAYS	