

Product Safety Data Sheet

Huizhou Desay Battery Co., Ltd.

Reference number: PSDS-RLI-2018MR

Product Name: Rechargeable Lithium-Ion Battery

Issued and Revised Date: 01-Jan.-2018

1. PRODUCT AND COMPANY IDENTIFICATION

- ✧ Product Name: Lithium-Ion Rechargeable Battery
- ✧ Applicable Models/Sizes: LI23S001A(48.84Wh), LI23S002A(49.95Wh), LI23I001A(49.95Wh), LI34I002A(97.68Wh), LI11S001A(6.66Wh), LI23I002A(53.28Wh), LI11S002A(5.55Wh), LI34I001A(66.6Wh), LI24I001A(44.4Wh), LI12S001A(6.66Wh), LI23I003A(63.28Wh), LI11I001A(6.66Wh), LI12I002A(18.5Wh), LI12I003A(18.5Wh), LI13I001A(28.86Wh), LI23S005A(55.5Wh), LI13S003A(27.75Wh), LI24I004A(84.56Wh), LI24I005A(84.56Wh), LI11C001A(0.87Wh), LI12I001B(14.44Wh), LI22S001A(35.52Wh)
- ✧ Company Identification: Huizhou Desay Battrey Co., Ltd.
- ✧ Address: No.15 , Zhongkai High & Technology Development Zone, Huizhou, Guangdong, China
- ✧ Telephone number: +86-752-2629810

2. HAZARDS IDENTIFICATION

For the battery cell, chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery cell case will be breached at the extreme, hazardous materials may be released.

Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted.

- ✧ GHS classification: Not available
(This product is outside the scope of GHS system since it's considered as an "article".)
- ✧ Most important hazard and effects
Human health effects:
 - Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.
 - Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and stimulation on the skin.
 - Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and stimulation on the eye. Especially, substance that causes a strong inflammation of the eyes is contained.
- Environmental effects: Since a battery cell remains in the environment, do not throw out it into the environment.
- ✧ Specific hazards:
 - If the electrolyte contacts with water, it will generate detrimental hydrogen fluoride.
 - Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Information about the chemical nature of product: *1

Portion	Material name	CAS No.	Concentration range
Positive electrode	Lithium transition metal (Li[M]m[O]n*2)	12190-79-3	20~60
		12057-17-9	
		182442-95-1	
Positive electrode's base	Aluminum	7429-90-5	1~10
Negative electrode	Carbon	7782-42-5	10~30
		7440-44-0	
Negative electrode's base	Copper	7440-50-8	1~15
Electrolyte	Ethyl methyl carbonate Diethyl carbonate Ethylene carbonate	623-53-0	5~25
		105-58-8	
		96-49-1	
Outer case and inert components	Iron	7439-89-6	1~30
	Aluminum	7429-90-5	
	-	Various	Balance

*1 Not every product includes all of these materials.

*2 The letter M means transition metal and candidates of M are Co, Mn and Ni. One compound includes one or more of these metals and one product includes one or more of the compounds.

The letter m and n means the number of atoms.

4. FIRST-AID MEASURES

Spilled internal cell materials

◇ Inhalation:

Make the victim blow his/her nose, gargle. Seek medical attention if necessary.

◇ Skin contact:

Remove contaminated clothes and shoes immediately. Wash extraneous matter or contact region with soap and plenty of water immediately.

◇ Eye contact:

Do not rub one's eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

A battery and spilled internal cell materials

◇ Ingestion:

Make the victim vomit. When it is impossible or the feeling is not well after vomiting, seek medical attention.

5. FIRE-FIGHTING MEASURES

◇ Suitable extinguishing media: Plenty of water, carbon dioxide gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.

◇ Specific hazards: Corrosive gas may be emitted during fire.

◇ Specific methods of fire-fighting: When the battery burns with other combustibles simultaneously, take fire-extinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible.

- ✧ Special protective equipment for firefighters:
 - Respiratory protection: Respiratory equipment of a gas cylinder style or protection-against-dust mask
 - Hand protection: Protective gloves
 - Eye protection: Goggle or protective glasses designed to protect against liquid splashes
 - Skin and body protection: Protective cloth

6. ACCIDENTAL RELEASE MEASURES

Spilled internal cell materials, such as electrolyte leaked from a battery cell, are carefully dealt with according to the followings.

- ✧ Precautions for human body:
 - Remove spilled materials with protective equipment (protective glasses and protective gloves). Do not inhale the gas as much as possible. Moreover, avoid touching with as much as possible.
- ✧ Environmental precautions: Do not throw out into the environment.
- ✧ Method of cleaning up: the spilled solids are put into a container. The leaked place is wiped off with dry cloth.
- ✧ Prevention of secondary hazards: avoid re-scattering. Do not bring the collected materials close to fire.

7. HANDLING AND STORAGE

- ✧ Handling Suggestions
 - Do not connect the positive terminal to the negative terminal with electrical wire or chain.
 - Avoid polarity reverse connection when installing the battery to an instrument.
 - Do not wet the battery with water, seawater, drink or acid; or expose to strong oxidizer.
 - Do not damage or remove the external tube/plastic shell.
 - Keep the battery away from heat and fire.
 - Do not disassemble or reconstruct the battery; or solder the battery directly.
 - Do not give a mechanical shock or deform.
 - Do not use unauthorized charger or other charging method. Terminate charging when the charging process doesn't end within specified time.
- ✧ Storage
 - Do not store the battery with metalware, water, seawater, strong acid or strong oxidizer.
 - Make the charge amount 30~50% then store at room temperature or less (temperature=-20~35℃) in a dry (humidity: 45~85%) place. Avoid direct sunlight, high temperature, and high humidity.
 - Use insulative and adequately strong packaging material to prevent short circuit between positive and negative terminal when the packaging breaks during normal handling.
 - Do not use conductive or easy to break packaging material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION(WHEN THE ELECTROLYTE LEAKS)

- ✧ Control parameters
 - ACGIH has not been mentioned control parameter of electrolyte.
- ✧ Personal protection equipment
 - Respiratory protection: Respirator with air cylinder, dust mask
 - Hand protection: Protective gloves
 - Eye protection: Goggle or protective glasses designed to protect against liquid splashes

Skin and body protection: Working clothes with long sleeve and long trousers

9. PHYSICAL AND CHEMICAL PROPERTIES

- ◇ Appearance
 - Physical state: Solid
 - Form: Cylindrical or Prismatic or Pouch (laminated)
 - Color: Various colors
 - Odor: No odor

10. STABILITY AND REACTIVITY

- ◇ Stability: Stable under normal use
- ◇ Hazardous reactions occurring under specific conditions
 - Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes, deformation, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Avoid to be exposed to direct sunlight and high humidity.
 - Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.
 - Hazardous decomposition products: Acrid or harmful gas is emitted during fire.

11. TOXICOLOGICAL INFORMATION

Organic Electrolyte

- ◇ Acute toxicity:
 - LD_{50} , oral-Rat 2,000mg/kg or more
- ◇ Irritating nature: Irritative to skin and eye

12. ECOLOGICAL INFORMATION

- ◇ Persistence/degradability:
 - Since a battery and the internal materials remain in the environment, do not bury or throw out into the environment.

13. DISPOSAL CONSIDERATIONS

- ◇ Recommended methods for safe and environmentally preferred disposal:

Product (waste from residues)

Do not throw out a used battery. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery contaminates, dispose as industrial wastes subject to special control.

14. TRANSPORT INFORMATION

In the case of transportation, avoid exposure to high temperature and prevent the formation of any condensation. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo

piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to section 7-HANDLING AND STORAGE also.

UN regulation

- ✧ UN number:
 - 3480 (Lithium ion batteries)
 - 3481 (Lithium ion batteries contained in equipment or packed in equipment)
- ✧ Proper shipping name:
 - “Lithium ion batteries”, “Lithium ion batteries contained in equipment” or “Lithium ion batteries packed with equipment”
- ✧ Class:9*

**Although this product meets the criteria of “dangerous goods” and are classified as “lithium ion batteries”, depending on the battery’s total capacity in the packing, etc., they may not be subject to the fully regulated provisions.*

Regulation depend on region and transportation mode

- ✧ Worldwide - Air transportation:
 - ICAO/IATA-DGR “packing instruction 965 section II ,Lithium Ion Batteries (limited to a maximum of 30% SOC)” or “packing instruction 966 section II” or “packing instruction 967 section II”
- ✧ Worldwide - Ocean transportation:
 - IMO-IMDG Code [special provision 188]
- ✧ Europe - Ground transportation:
 - ADR [special provision 188]

**Instructions or provisions in the box brackets are conditions to make the battery exempted from full regulation.*

15. REGULATORY INFORMATION

- ✧ Regulations specifically applicable to the product:
 - Wastes Disposal and Public Cleaning Law [Japan]
 - Law for Promotion of Effective Utilization of resources [Japan]
 - US Department of Transportation 49 Code of Federal Regulations [USA]

**About overlapping regulations, please refer to Section 14-TRANSPORT INFORMATION.*

16. OTHER INFORMATION

- ✧ This safety data sheet is offered an agency who handles this product to handle it safely.
- ✧ The agency should utilize this safety data sheet effectively (put it up, educate person in charge) and take proper measures.
- ✧ ***The information contained in this safety data sheet is based on the present state of knowledge and current legislation.***
- ✧ The safety data sheet provides guidance on health, safety and environment aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Reference

- Dangerous Goods Regulations – the 2018 Edition of the ICAO Technical Instruction for the Safe Transport of Dangerous Goods by Air and the 59th Edition of the IATA Dangerous Goods Regulations (DGR).
- IMDG Code – 2016 Edition: International Maritime Organization (IMO)
- The European Agreement concerning the International Carriage of Dangerous Goods by Road –2017: The United Nations Economic Commission for Europe (UNECE)

(End)